# Safety Data Sheet

## according to OSHA Hazard Communication

29 CFR Part 1910.1200

## Section 1. Identification

Product Information:	22L-E006
Product Name:	TOUGHLINE® BLUE TRAFFIC SAFETY PAINT
Recommended Use:	Liquid Paint
Application Method:	See Product Data Sheet
Supplied by:	Aexcel Corporation 7373 Production Drive. Mentor, OH 44060
Emergency Telephone: Safety Data Sheet Coordinator:	Chemtrec: 800-424-9300 mmann@aexcelcorp.com

## Section 2. Hazard(s) identification

EMERGENCY OVERVIEW: Flammable liquid and vapor.

#### GHS Classification Carc. 2, Flam. Liq. 2

#### Symbol(s) of Product



#### Signal Word Danger

#### **Possible Hazards**

33% of the mixture consists of ingredients of unknown acute toxicity

## GHS HAZARD STATEMENTS

GIIS HAZAND STATEMENTS		
Carcinogenicity, category 2	H351	Suspected of causing cancer.
Flammable Liquid, category 2	H225	Highly flammable liquid and vapour.
GHS LABEL PRECAUTIONARY STAT	EMENTS	
P201	Obtain sp	ecial instructions before use.
P210	Keep awa smoking.	y from heat, hot surfaces, sparks, open flames and other ignition sources. No
P233	Keep cont	ainer tightly closed.
P280	Wear prot	ective gloves/protective clothing/eye protection/face protection.
P281	Use perso	nal protective equipment as required.
P303+P361+P353	IF ON SKI water/sho	N (or hair): Take off immediately all contaminated clothing. Rinse skin with wer.
P308+P313	IF expose	d or concerned: Get medical advice/attention.
P370+P378	In case of	fire: Use dry chemical, carbon dioxide, or foam to extinguish.
P403+P235	Store in a	well-ventilated place. Keep cool.
		Page 1/7

Product:	22L	-E006
----------	-----	-------

P405	Store locked up.
P501	Dispose of contents/container in accordance with local rules and regulations.
GHS SDS PRECAUTIONARY STATEM	ENTS
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.

## Section 3. Composition/Information on ingredients

<u>Chemical Name</u> DIMETHYL CARBONATE/ DIMETHYL ESTER	CAS-No. 616-38-6	<u>Wt. %</u> 10-25	GHS Symbols GHS02	GHS Statements H225
ACETONE TOLUENE	67-64-1 108-88-3	2.5-10 1.0-2.5	GHS02-GHS07 GHS02-GHS07- GHS08	H225-320-335-336 H225-304-315-336-361-373
XYLENE	1330-20-7	1.0-2.5	GHS02-GHS07- GHS08	H226-304-312-315-319-332-335 -351-361-373

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

#### Section 4. First-aid measures



**FIRST AID - INHALATION:** Move to fresh air in case of accidental inhalation of vapors or decomposition products. Move to fresh air. Oxygen or artificial respiration if needed.

**FIRST AID - SKIN CONTACT:** If skin irritation persists, call a physician. Wash off immediately with plenty of water. Wash off immediately with soap and plenty of water. Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes.

FIRST AID - EYE CONTACT: Rinse with plenty of water.

**FIRST AID - INGESTION:** Call a physician or Poison Control Center immediately. Consult a physician. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person.

#### Section 5. Fire-fighting measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: Remove all sources of ignition.

**SPECIAL FIREFIGHTING PROCEDURES:** Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

EXTINGUISHING MEDIA: Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam

#### Section 6. Accidental release measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Soak up with inert absorbent material and dispose of as hazardous waste.

Section 7. Handling and storage



**HANDLING:** Containers of this material may be hazardous when emptied. Handle in accordance with good industrial hygiene and safety practice. Keep out of reach of children.

**STORAGE:** Harmful - Store away from foodstuffs. Keep containers tightly closed. Keep in a well-ventilated place. Keep locked-up. Keep refrigerated. For Industrial Use Only

## Section 8. Exposure controls/personal protection

Ingredients with Occupational Exposure Limits						
<u>Chemical Name</u>	ACGIH TLV-TWA	ACGIH-TLV STEL	<u>OSHA PEL-TWA</u>	OSHA PEL-CEILING		
DIMETHYL CARBONATE/ DIMETHYL ESTER	NE	NE	NE	NE		
ACETONE	250 ppm	500 ppm	1000 ppm	NE		
TOLUENE	20 ppm	150 ppm	200 ppm	300 ppm		
XYLENE	100 ppm	150 ppm	100 ppm	NE		

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

#### **Personal Protection**



**RESPIRATORY PROTECTION:** In the case of respirable dust and/or fumes, use self-contained breathing apparatus.



SKIN PROTECTION: Impervious gloves.



**EYE PROTECTION:** Safety glasses with side-shields.



OTHER PROTECTIVE EQUIPMENT: Impervious clothing.



**HYGIENIC PRACTICES:** Contaminated work clothing should not be allowed out of the workplace. General industrial hygiene practice. Keep working clothes separately.

#### Section 9. Physical and Chemical Properties

132 - 536 Characteristic Heavy Liquid NE NE 180.80 Liquid		Odor Thi Evaporat Specific pH: Viscosity	reshold: tion Rate: Gravity: /:	NE NE	9	
ation legend)						
VAPOR DENSITY	<b>EVAPORATION</b>	RATE	BOILING POIN	T	<u>VP mmHg</u>	<u>at DEG. F</u>
3.10	NE		195		55.50	77
NE	NE		132		180.80	68
3.10	2.00		231		21.00	68
0.87	NE		279		9.00	77
	Characteristic Heavy Liquid NE NE 180.80 Liquid ation legend) VAPOR DENSITY 3.10 NE 3.10	Characteristic Heavy Liquid NE 180.80 LiquidSummary LiquidVAPOR DENSITYEVAPORATION3.10NENE 3.10NE3.102.00	CharacteristicOdor Thr EvaporatHeavy LiquidEvaporatNEpH:180.80ViscosityLiquidFlash Poation legend)EVAPORATION RATE3.10NENENE3.10NE3.102.00	CharacteristicOdor Threshold:Heavy LiquidEvaporation Rate:NESpecific Gravity:NEpH:180.80Viscosity:LiquidFlash Point, °C:attion legend)EVAPORATION RATEVAPOR DENSITYEVAPORATION RATEBOILING POINT3.10NE195NENE1323.102.00231	Characteristic Heavy Liquid NE NE 180.80 LiquidOdor Threshold: Evaporation Rate: 9H: Viscosity: Flash Point, °C: 17, NE 180.80 LiquidNE NE NE 180.80 CiquidNE NE NE 180.80 Viscosity: 1.389 NE NE 180.80 LiquidNE PH: NE NE 180.80 Viscosity: NE 180.80 NE 180.80 LiquidNE PH: NE NE 180.80 Viscosity: NE 180.80 NE 180.80 LiquidNE PH: NE NE 180.80 Viscosity: 	Characteristic Heavy Liquid NE NE LiquidOdor Threshold: NE Evaporation Rate: Specific Gravity: PH: Flash Point, °C: -17, °F 1.4NE 180.80 LiquidPH: Flash Point, °C: -17, °F 1.4NE 180.80 LiquidNE Flash Point, °C: -17, °F 1.4VAPOR DENSITYEVAPORATION RATE FlashBOILING POINT 195VAPOR DENSITYNE NE 180.80195NE 3.10NE132180.80 21.00

#### Section 10. Stability and reactivity

STABILITY: Stable under normal conditions. Stable if used as directed.

**CONDITIONS TO AVOID:** Avoid contact with skin, eyes and clothing.

INCOMPATIBILITY: Keep away from strong oxidizing agents, heat and open flames.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Monoxide, Carbon Dioxide

#### Section 11. Toxicological information



Practical Experiences

**EFFECT OF OVEREXPOSURE - INHALATION:** Inhalation may cause irritation to the respiratory tract (nose, mouth, mucous membranes).

**EFFECT OF OVEREXPOSURE - SKIN CONTACT:** Local ventilation of emission sources may be necessary to maintain ambient concentrations below recommended exposure limits.

EFFECT OF OVEREXPOSURE - EYE CONTACT: Direct eye contact may cause irritation.

EFFECT OF OVEREXPOSURE - INGESTION: Harmful: may cause lung damage if swallowed.

**CARCINOGENICITY: No Information** 

#### **Acute Toxicity Values**

The acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Name according to EEC	Oral LD50	Dermal LD50	Vapor LC50
616-38-6	DIMETHYL CARBONATE/ DIMETHYL	N.I.	N.I.	N.I.
	ESTER			
67-64-1	ACETONE	N.I.	N.I.	N.I.
108-88-3	TOLUENE	5580	12196	12500
1330-20-7	XYLENE	4300	2000	N.I.

N.I. - No Information

## Section 12. Ecological information

ECOLOGICAL INFORMATION: Do not contaminate ponds, waterways or ditches with chemical or used container.

#### Section 13. Disposal considerations



Product

DISPOSAL METHOD: Contact waste disposal services. Dispose of in accordance with all local, state and federal regulations.

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Soak up with inert absorbent material and dispose of as hazardous waste.

#### Section 14. Transport information

SPECIAL TRANSPORT PRECAUTIONS: No Information

DOT Proper ShippingPaint, Flammable LiquidDOT Technical Name:PaintDOT Hazard Class:3DOT UN/NA Number:1263

Packing Group: Hazard SubClass: Resp. Guide Page: II No Information 128

#### Section 15. Regulatory information

#### **U.S. Federal Regulations:**

#### **CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Carcinogenicity

#### SARA SECTION 312:

Chemical Name	CAS-No.
ACETONE	67-64-1
TOLUENE	108-88-3
XYLENE	1330-20-7

#### SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	CAS-No.
ACETONE	67-64-1
TOLUENE	108-88-3
XYLENE	1330-20-7
CUMENE	98-82-8

#### TOXIC SUBSTANCES CONTROL ACT:

All components of this material are listed on the US Toxic Substance Control Act (TSCA inventory).

#### U.S. State Regulations:

#### **NEW JERSEY RIGHT-TO-KNOW:**

The following materials are non-hazardous, but are among the top five components in this product.

Chemical Name	CAS-No.
LIMESTONE	1317-65-3
BUTYL METHACRYLATE COPOLYMER	

#### PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3%.

<u>Chemical Name</u> LIMESTONE BUTYL METHACRYLATE COPOLYMER CAS-No. 1317-65-3

#### **CALIFORNIA PROPOSITION 65 CARCINOGENS**



The following ingredients present in the product are known to the state of California to cause Cancer:

Chemical Name DI-ISONONYL PHTHALATE TITANIUM DIOXIDE <u>CAS-No.</u> 28553-12-0 13463-67-7

#### Product: 22L-E006

#### CUMENE

98-82-8

#### **CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS**

The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

#### Chemical Name

TOLUENE

CAS-No. 108-88-3

### International Regulations: As follows -

#### CANADIAN WHMIS:

All components of this material are listed on the Domestic Substance List.

WHMIS Class: No Information

#### Section 16. Other information, including date of preparation of the last revision

Revision Da	ate:	4/10/2024			Sup	percedes Date:	1/27/2021
Reason for	revision:	vision:Revision Description Changed Product Composition Changed Substance and/or Product Properties Changed in Section(s): 01 - Product Information 02 - Hazards Identification 08 - Exposure Controls/Personal Protection 09 - Physical & Chemical Information 15 - Regulatory Information Substance Chemical Name Changed Substance Hazardous Flag Changed Substance Hazard Threshold % Changed Revision Statement(s) Changed					
Datasheet produced by: Regulatory Department							
HMIS Rati	ngs:						
Health:	2	Flammability:	3	Reactivity:	0	Personal Protection:	X


100

Volatile Organic Compounds, gr/ltr:

#### Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H320	Causes eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
Icons for GHS P	ictograms shown in Section 3 describing each ingredient:

Icons for GHS Pictograms shown in Section 3 describing each ingredient:



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

No Information