# Safety Data Sheet

# according to OSHA Hazard Communication

29 CFR Part 1910.1200

### Section 1. Identification

Product Information:	25Y-G015
Product Name:	ROADZILLA® YELLOW 98:2 EXTRUDE-TYPE I-STENCIL
Recommended Use:	Liquid Paint
Application Method:	See Product Data Sheet
Supplied by:	Aexcel Corporation 7373 Production Drive. Mentor, OH 44060
Emergency Telephone: Safety Data Sheet Coordinator:	Chemtrec: 800-424-9300 mmann@aexcelcorp.com

#### Section 2. Hazard(s) identification

EMERGENCY OVERVIEW: Flammable liquid and vapor.

#### **GHS Classification**

Flam. Liq. 2, Skin Irrit. 2, Skin Sens. 1

#### Symbol(s) of Product



Signal Word Danger

#### Possible Hazards

16% of the mixture consists of ingredients of unknown acute toxicity

#### GHS HAZARD STATEMENTS

Flammable Liquid, category 2	H225	Highly flammable liquid and vapour.
Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
GHS LABEL PRECAUTIONARY STATI	EMENTS	
P210	Keep away	from heat, hot surfaces, sparks, open flames and other ignition sources. No
	smoking.	
P233	Keep contai	iner tightly closed.
P261	Avoid breat	hing dust/fume/gas/mist/vapours/spray.
P264	Wash thoro	ughly after handling.
P272	Contaminat	ed work clothing should not be allowed out of the workplace.
P280	Wear protect	ctive gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN	I: Wash with plenty of water.
P303+P361+P353	IF ON SKIN water/show	l (or hair): Take off immediately all contaminated clothing. Rinse skin with er.

P321	Specific treatment (see on this label).
P332+P313	If skin irritation occurs: Get medical advice/attention.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P370+P378	In case of fire: Use dry chemical, carbon dioxide, or foam to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local rules and regulations.
GHS SDS PRECAUTIONARY STATEM	ENTS
GHS SDS PRECAUTIONARY STATEM P240	ENTS Ground/bond container and receiving equipment.
P240	Ground/bond container and receiving equipment.
P240 P241	Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment.

#### Section 3. Composition/Information on ingredients

Chemical Name	CAS-No.	<u>Wt. %</u>	GHS Symbols	GHS Statements
METHYL METHACRYLATE	80-62-6	2.5-10	GHS07	H315-317-335
N-BUTYL ACRYLATE	141-32-2	2.5-10	GHS02-GHS07	H226-315-317-319-332-335

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

#### Section 4. First-aid measures



FIRST AID - INHALATION: Move to fresh air.

FIRST AID - SKIN CONTACT: Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes.

**FIRST AID - EYE CONTACT:** In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Rinse with plenty of water.

FIRST AID - INGESTION: Call a physician immediately. Do not induce vomiting without medical advice.

#### Section 5. Fire-fighting measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: Remove all sources of ignition.

**SPECIAL FIREFIGHTING PROCEDURES:** Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

EXTINGUISHING MEDIA: Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam

#### Section 6. Accidental release measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Soak up with inert absorbent material and dispose of as hazardous waste.

#### Section 7. Handling and storage



HANDLING: Containers of this material may be hazardous when emptied. Handle in accordance with good industrial hygiene and safety practice.

**STORAGE:** Harmful - Store away from foodstuffs. Keep containers tightly closed. Keep in a well-ventilated place. Keep locked-up. For Industrial Use Only

#### Section 8. Exposure controls/personal protection

Ingredients with Occupational Exposure Limits				
Chemical Name	ACGIH TLV-TWA	ACGIH-TLV STEL	<u>OSHA PEL-TWA</u>	OSHA PEL-CEILING
METHYL METHACRYLATE N-BUTYL ACRYLATE	50 ppm 2 ppm	100 ppm NE	100 ppm 10 ppm	NE NE

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

#### **Personal Protection**

**RESPIRATORY PROTECTION:** In the case of respirable dust and/or fumes, use self-contained breathing apparatus.



SKIN PROTECTION: Impervious gloves.



EYE PROTECTION: Safety glasses with side-shields.



**OTHER PROTECTIVE EQUIPMENT:** Impervious clothing.



HYGIENIC PRACTICES: General industrial hygiene practice.

#### Section 9. Physical and Chemical Properties

Boiling Range (F): Odor: Appearance: Solubility in Water: Freeze Point: Vapor Pressure (mm Hg): Physical State:	255 - 392 Characteristic Heavy Liquid NE NE 40.00 Liquid	Evapora Specific pH: Viscosit	rreshold: N ttion Rate: 3 Gravity: 1 N y: N	.60 IE 3.10 .919 IE IE 0, °F 50	
(See section 16 for abbrevi	ation legend)				
CHEMICAL NAME	VAPOR DENSITY	EVAPORATION RATE	<b>BOILING POINT</b>	<u>VP mmHg</u>	<u>at DEG. F</u>
METHYL METHACRYLAT	E3.60	3.10	212	40.00	68
N-BUTYL ACRYLATE	0.899	NA	298	4.30	68
Section 10. Stability	and reactivity				

STABILITY: Stable under normal conditions. Stable if used as directed.

CONDITIONS TO AVOID: Avoid contact with skin, eyes and clothing.

**INCOMPATIBILITY:** Strong oxidizing agents. Keep away from strong oxidizing agents, heat and open flames.

HAZARDOUS DECOMPOSITION PRODUCTS: No decomposition if used as directed.

#### Section 11. Toxicological information



#### Practical Experiences

**EFFECT OF OVEREXPOSURE - INHALATION:** Inhalation may cause irritation to the respiratory tract (nose, mouth, mucous membranes).

**EFFECT OF OVEREXPOSURE - SKIN CONTACT:** Local ventilation of emission sources may be necessary to maintain ambient concentrations below recommended exposure limits.

EFFECT OF OVEREXPOSURE - EYE CONTACT: Direct eye contact may cause irritation.

EFFECT OF OVEREXPOSURE - INGESTION: Harmful: may cause lung damage if swallowed.

CARCINOGENICITY: No Information

#### Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Name according to EEC	Oral LD50	<u>Dermal LD50</u>	Vapor LC50
80-62-6	METHYL METHACRYLATE	N.I.	N.I.	N.I.
141-32-2	N-BUTYL ACRYLATE	N.I.	N.I.	N.I.

N.I. - No Information

#### Section 12. Ecological information

ECOLOGICAL INFORMATION: Do not contaminate ponds, waterways or ditches with chemical or used container.

#### Section 13. Disposal considerations



Product

**DISPOSAL METHOD:** Contact waste disposal services. Dispose of in accordance with all local, state and federal regulations.

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Soak up with inert absorbent material and dispose of as hazardous waste.

#### Section 14. Transport information

#### SPECIAL TRANSPORT PRECAUTIONS: No Information

DOT Proper Shipping DOT Technical Name: DOT Hazard Class: DOT UN/NA Number:

Paint, Flammable Liquid Paint 3 1263 Packing Group: Hazard SubClass: Resp. Guide Page: II No Information 128

#### Section 15. Regulatory information

#### **U.S. Federal Regulations:**

#### **CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Skin Corrosion or Irritation, Respiratory or Skin Sensitization

#### SARA SECTION 312:

Chemical Name	CAS-No.
METHYL METHACRYLATE	80-62-6
N-BUTYL ACRYLATE	141-32-2

#### SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical Name	CAS-No.
METHYL METHACRYLATE	80-62-6
N-BUTYL ACRYLATE	141-32-2
1-METHYL-2-PYRROLIDONE	872-50-4
XYLENE	1330-20-7
ETHYL BENZENE	100-41-4

#### TOXIC SUBSTANCES CONTROL ACT:

All components of this material are listed on the US Toxic Substance Control Act (TSCA inventory).

#### U.S. State Regulations:

#### **NEW JERSEY RIGHT-TO-KNOW:**

The following materials are non-hazardous, but are among the top five components in this product.

Chemical Name	<u>CAS-No.</u>
LIMESTONE	1317-65-3
AASHTO TYPE I, UNCOATED BEADS	MIXTURE
AGGREGATE	MIXTURE

#### PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3%.

Chemical Name	CAS-No.
LIMESTONE	1317-65-3
AASHTO TYPE I, UNCOATED BEADS	MIXTURE
AGGREGATE	MIXTURE
BUTYL METHACRYLATE COPOLYMER	28262-63-7
YELLOW 65	6528-34-3

#### **CALIFORNIA PROPOSITION 65 CARCINOGENS**



The following ingredients present in the product are known to the state of California to cause Cancer:

Chemical Name	CAS-No.
TITANIUM DIOXIDE	13463-67-7
ETHYL BENZENE	100-41-4

#### **CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS**

The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

CAS-No. 872-50-4

#### Chemical Name

1-METHYL-2-PYRROLIDONE	

## International Regulations: As follows -

#### CANADIAN WHMIS:

All components of this material are listed on the Domestic Substance List.

WHMIS Class: No Information

#### Section 16. Other information, including date of preparation of the last revision

<b>Revision Date:</b> 4/19/2024				Sup	percedes Date:	4/23/2021		
Reason for	revision:	Substance 01 - Produ 02 - Hazar 08 - Expos 09 - Physic Substance Substance Substance	Product Composition Changed Substance and/or Product Properties Changed in Section(s): 01 - Product Information 02 - Hazards Identification 08 - Exposure Controls/Personal Protection 09 - Physical & Chemical Information Substance Chemical Name Changed Substance Hazardous Flag Changed Substance Hazard Threshold % Changed Revision Statement(s) Changed					
Datasheet p	oroduced by:	Regulatory	Regulatory Department					
HMIS Ratings:								
Health:	2	Flammability:	3	Reactivity:	2	Personal Protection:	X	

6

Volatile Organic Compounds, gr/ltr:

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:



#### Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

No Information