# Safety Data Sheet



# according to OSHA Hazard Communication 29 CFR Part 1910.1200

## Section 1. Identification

Product Information: 75W-D012

Product Name: LANE LITE® WHITE POLYESTER TRAFFIC MARKING PAINT

Recommended Use: Liquid Paint

Application Method: See Product Data Sheet

Supplied by: Aexcel Corporation

7373 Production Drive. Mentor, OH 44060

Emergency Telephone: Chemtrec: 800-424-9300
Safety Data Sheet Coordinator: mmann@aexcelcorp.com

## Section 2. Hazard(s) identification

EMERGENCY OVERVIEW: Flammable liquid and vapor.

#### **GHS Classification**

Acute Tox. 4 Inhalation, Asp. Tox. 1, Carc. 2, Eye Irrit. 2A, Flam. Liq. 3, Skin Irrit. 2, STOT RE 1, STOT SE 3 NE, STOT SE 3 RTI

#### Symbol(s) of Product







Signal Word

Danger

#### **GHS HAZARD STATEMENTS**

Acute Toxicity, Inhalation, category 4

Aspiration Hazard, category 1	H304	May be fatal if swallowed and enters airways.
Carcinogenicity, category 2	H351	Suspected of causing cancer.
Eye Irritation, category 2A	H319	Causes serious eye irritation.
Flammable Liquid, category 3	H226	Flammable liquid and vapour.

Skin Irritation, category 2 H315 Causes skin irritation.

STOT, repeated exposure, category 1 H372 Causes damage to organs through prolonged or repeated exposure.

Harmful if inhaled.

STOT, single exposure, category 3, NE H336 May cause drowsiness or dizziness. STOT, single exposure, category 3, RTI H335 May cause respiratory irritation.

H332

#### **GHS LABEL PRECAUTIONARY STATEMENTS**

P201 Obtain special instructions before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P281 Use personal protective equipment as required.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P302+P352 IF ON SKIN: Wash with plenty of water.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.
P312 Call a POISON CENTER/doctor if you feel unwell.

P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

P332+P313 If skin irritation occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use dry chemical, carbon dioxide, or foam to extinguish.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local rules and regulations.

#### **GHS SDS PRECAUTIONARY STATEMENTS**

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.
P270 Do not eat, drink or smoke when using this product.

P363 Wash contaminated clothing before reuse.

## Section 3. Composition/Information on ingredients

Chemical Name CAS-No. Wt. % GHS Symbols GHS Statements

STYRENE MONOMER 100-42-5 25-50 GHS02-GHS07- H226-304-315-319-332-335-336

GHS08 -351-372

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

## Section 4. First-aid measures



FIRST AID - INHALATION: Move to fresh air in case of accidental inhalation of vapors.

FIRST AID - SKIN CONTACT: Wash off immediately with plenty of water.

FIRST AID - EYE CONTACT: In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Rinse with plenty of water.

FIRST AID - INGESTION: Call a physician immediately. Do not induce vomiting

## Section 5. Fire-fighting measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: Remove all sources of ignition.

**SPECIAL FIREFIGHTING PROCEDURES:** Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

EXTINGUISHING MEDIA: Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam

#### Section 6. Accidental release measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Soak up with inert absorbent material and dispose of as hazardous waste.

# Section 7. Handling and storage





**HANDLING:** Containers of this material may be hazardous when emptied. Handle in accordance with good industrial hygiene and safety practice.

**STORAGE:** Harmful - Store away from foodstuffs. Keep containers tightly closed. Keep in a well-ventilated place. Keep locked-up. For Industrial Use Only

## Section 8. Exposure controls/personal protection

Ingredients with Occupational Exposure Limits

<u>Chemical Name</u> <u>ACGIH TLV-TWA</u> <u>ACGIH-TLV STEL</u> <u>OSHA PEL-TWA</u> <u>OSHA PEL-CEILING</u>

STYRENE MONOMER 20 ppm 40 ppm 100 ppm 200 ppm

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

#### **Personal Protection**



RESPIRATORY PROTECTION: In the case of respirable dust and/or fumes, use self-contained breathing apparatus.



SKIN PROTECTION: Impervious gloves.



**EYE PROTECTION:** Safety glasses with side-shields.



**OTHER PROTECTIVE EQUIPMENT:** No Information



**HYGIENIC PRACTICES:** General industrial hygiene practice. Remove and wash contaminated clothing before re-use.

# Section 9. Physical and Chemical Properties

293 - 381 Vapor Density: Boiling Range (F): 3.60 Odor Threshold: Odor: Characteristic ΝE Appearance: Heavy Liquid **Evaporation Rate:** 0.49 Specific Gravity: Solubility in Water: NE 1.383 Freeze Point: NE pH: NE Vapor Pressure (mm Hg): 4.30 Viscosity: NE 31, °F 87.8 Flash Point, °C:

(See section 16 for abbreviation legend)

CHEMICAL NAME VAPOR DENSITY EVAPORATION RATE **BOILING POINT** VP mmHg at DEG. F

STYRENE MONOMER 293 4.3 0.49 68

## Section 10. Stability and reactivity

STABILITY: Stable if used as directed. Ustable @ high temperatures and extended storage.

CONDITIONS TO AVOID: Avoid contact with skin, eyes and clothing.

Liquid

INCOMPATIBILITY: Keep away from strong oxidizing agents, heat and open flames. HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Monoxide, Carbon Dioxide

## Section 11. Toxicological information



**Physical State:** 

#### **Practical Experiences**

EFFECT OF OVEREXPOSURE - INHALATION: Inhalation may cause irritation to the respiratory tract (nose, mouth, mucous membranes).

EFFECT OF OVEREXPOSURE - SKIN CONTACT: Local ventilation of emission sources may be necessary to maintain ambient concentrations below recommended exposure limits.

EFFECT OF OVEREXPOSURE - EYE CONTACT: Direct eye contact may cause irritation.

EFFECT OF OVEREXPOSURE - INGESTION: Harmful: may cause lung damage if swallowed.

**CARCINOGENICITY:** No Information

#### **Acute Toxicity Values**

The acute effects of this product have not been tested. Data on individual components are tabulated below:

Oral LD50 CAS-No. Name according to EEC Dermal LD50 Vapor LC50 100-42-5 STYRENE MONOMER N.I. N.I. N.I.

N.I. - No Information

## Section 12. Ecological information

ECOLOGICAL INFORMATION: Do not contaminate ponds, waterways or ditches with chemical or used container.

#### Section 13. Disposal considerations



**Product** 

DISPOSAL METHOD: Contact waste disposal services. Dispose of in accordance with all local, state and federal regulations.

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Soak up with inert absorbent material and dispose of as hazardous waste.

## Section 14. Transport information

SPECIAL TRANSPORT PRECAUTIONS: No Information

DOT Proper Shipping Paint, Flammabe Liquid Packing Group: II

DOT Technical Name: Paint Hazard SubClass: No Information

DOT Hazard Class: 3 Resp. Guide Page: 128

DOT UN/NA Number: 1263

## Section 15. Regulatory information

## U.S. Federal Regulations:

#### **CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Carcinogenicity, Acute Toxicity (any route of exposure), Skin Corrosion or Irritation, Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure), Aspiration Hazard

#### **SARA SECTION 312:**

Chemical NameCAS-No.STYRENE MONOMER100-42-5

#### **SARA SECTION 313:**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

 Chemical Name
 CAS-No.

 STYRENE MONOMER
 100-42-5

 SOLIDS COBALT 12%
 136-52-7

 N,N-DIMETHYL ANALINE
 121-69-7

#### TOXIC SUBSTANCES CONTROL ACT:

All components of this material are listed on the US Toxic Substance Control Act (TSCA inventory).

#### U.S. State Regulations:

#### **NEW JERSEY RIGHT-TO-KNOW:**

The following materials are non-hazardous, but are among the top five components in this product.

<u>Chemical Name</u> <u>CAS-No.</u>

UNSATURATED POLYESTER RESIN NON-HAZARDOUS TITANIUM DIOXIDE 13463-67-7 MINEX 4 37244-96-5

#### PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3%.

<u>Chemical Name</u> <u>CAS-No.</u>

UNSATURATED POLYESTER RESIN NON-HAZARDOUS TITANIUM DIOXIDE 13463-67-7 MINEX 4 37244-96-5

**ALUMINUM SILICATE** 66402-68-4

#### **CALIFORNIA PROPOSITION 65 CARCINOGENS**



# WARNING

The following ingredients present in the product are known to the state of California to cause Cancer:

**Chemical Name** CAS-No. STYRENE MONOMER 100-42-5 TITANIUM DIOXIDE 13463-67-7

#### **CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS**

The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

No Proposition 65 Reproductive Toxins exist in this product.

International Regulations: As follows -

#### **CANADIAN WHMIS:**

All components of this material are listed on the Domestic Substance List.

WHMIS Class: No Information

## Section 16. Other information, including date of preparation of the last revision

**Revision Date:** Supercedes Date: 4/17/2024 1/28/2021

Reason for revision: **Product Composition Changed** 

Substance and/or Product Properties Changed in Section(s):

02 - Hazards Identification 05 - Flammability Information

08 - Exposure Controls/Personal Protection 09 - Physical & Chemical Information

15 - Regulatory Information

Substance Hazardous Flag Changed Substance Hazard Threshold % Changed Substance Chemical Name Changed

Revision Statement(s) Changed

Datasheet produced by: Regulatory Department

**HMIS Ratings:** 

Health:	1	Flammability:	3	Reactivity:	0	Personal Protection:	Х
---------	---	---------------	---	-------------	---	----------------------	---

#### Volatile Organic Compounds, gr/ltr: 418

#### Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure.

# Icons for GHS Pictograms shown in Section 3 describing each ingredient:



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

No Information